



INVESTOR IN PEOPLE

**PRIORITY
DOCUMENT**SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)The Patent Office
Concept House
Cardiff Road

Newport

South Wales

NP10 8QQ

REC'D 02 JUN 2004

WIPO

PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.


In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.




Signed

Dated 21 May 2004



The
Patent
Office



1/77

12MAY03 E06361-1 D02903
F01/7700 0.00-0310803-2

The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH

Request for grant of a patent
(fill in the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help fill in this form)

Your reference

11233P6 GB/AB

Patent application number
(The Patent Office will fill in this part)

0310803.2

10 MAY 2003

Full name, address and postcode of the or of each applicant *(underline all surnames)*

Reckitt Benckiser N.V.
Kantoorgebouw De Appelaer
De Fruittuinen 2-12
2132 NZ Hoofddorp
NETHERLANDS

Patents ADP number *(if you know it)*

07921075005 ✓

If the applicant is a corporate body, give the country/state of its incorporation

Netherlands

Title of the invention

Water-Softening Product

Name of your agent *(if you have one)*

Andrew Stephen Brown
Reckitt Benckiser plc
Group Patents Department
Dansom Lane
Hull
HU8-7DS-
United Kingdom

"Address for service" in the United Kingdom to which all correspondence should be sent *(including the postcode)*

Patents ADP number *(if you know it)*

08079311001 ✓

If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and *(if you know it)* the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application
(day / month / year)

Date of filing
(day / month / year)

Is a statement of inventorship and of right to grant of a patent required in support of this request? *(Answer 'Yes' if:*

Yes

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

5004/01765

Patents Form 1/77

Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form	--
Description	11
Claim(s)	3
Abstract	1
Drawing(s)	--

If you are also filing any of the following, state how many against each item.

Priority documents
Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and search (*Patents Form 9/77*) One ✓

Request for substantive examination (*Patents Form 10/77*) One ✓

Any other documents (please specify) FS1 ✓

I/We request the grant of a patent on the basis of this application.

Signature

Date

Andrew Stephen Brown

9 May 2003

Name and daytime telephone number of Person to contact in the United Kingdom

Andrew S Brown (01482) 582411

During

When an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

as

If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.

Write your answers in capital letters using black ink or you may type them.

If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.

If you have answered 'Yes' Patents Form 7/77 will need to be filed.

Once you have filled in the form you must remember to sign and date it.

For details of the fee and ways to pay please contact the Patents Office.

WATER-SOFTENING PRODUCT

The present invention relates to liquid water-softening compositions, especially compositions which
5 dissolve and disperse satisfactorily in water.

Water softening products are sold commercially (such as the product Calgon®) and are used to aid detergency and prevent the build up of scale in the washing machine
10 and on clothes, such products are described in EP-A1-0 628 627 (Benckiser), CH-577 937 (Lonza), WO-A1-95/21908 (Henkel) and EP-A2-0 622 449 (Huls).

The use of water-softening polymer polycarboxylates
15 in detergent formulas has provided multiple benefits such as calcium sequestration, crystal growth inhibition to minimize encrustation on fabrics, lime soap dispersancy, and particulate soil dispersion. Sequestration of
"hardness" metal-ions such as calcium and magnesium by
20 the polycarboxylates softens the water and increases detergency. Also sequestration of hardness ions by the polycarboxylates prevents the precipitation of salts of anionic surfactants, which if allowed to occur will lead to reduced detergency. Dispersion of particulate soil
25 such as clay by the polycarboxylates prevents the redeposition of soils on the fabric.

Conveniently it would be preferred that water-softening products could be added to the washing machine
30 as a liquid rather than as a solid product. Also it is preferable that the product has a viscosity which is greater than that of water.

Liquid water-softening compositions often contain up to 80 wt% water. Such compositions do not generally have any compatibility problems when being diluted with a large quantity of water.

5

GB2379214 describes an aqueous based water-softening composition thickened with xanthan gum.

10

Conveniently, it is preferred that such liquid water-softening products are added to the washing machine as convenient unit doses, encapsulated in a water-soluble polymer. However, such compositions contain little water and may gel when added to large volumes of water.

15

20

The invention relates to compositions in the form of a viscous composition, which is substantially free of water that contains water softening agents. Preferably the composition is transparent. The composition is highly concentrated with water softening actives incorporated by the use of solvents and has been specially developed with a low amount of water for encapsulation in water soluble packaging made of a water-soluble polymer, such as poly (vinylalcohol) [PVOH], cellulose, (HPMC), or gelatine, that dissolve easily in water.

25

30

35

Additional problems are to disperse and bring in solution during manufacture of the compositions a high amount of actives, in powder form, in a low amount of water and obtain a stable composition without any precipitation. The objective is achieved by producing a water softener composition in gel form containing a low amount of water by the use of organic solvents and a water-softening active that is preferably acidic, ideally containing at least one carboxylic acid, a part

neutralised acid polymer with an organic alkaline agent as the neutralising agent.

Accordingly the present invention provides a liquid
5 water-softening composition comprising:

- a) at least one water-softening active; and
- b) at least one organic solvent;

said composition containing less than 35 wt%, ideally less than 25 wt%, preferably less than 18 wt% of water.

10 Ideally the composition is transparent.

Larger amounts of water can be found in the composition which is chemically or physically bound.

15 Therefore, the amount of water is preferably less than 25 wt%, ideally less than 18wt%, preferably less than 15 wt% of free water. By free water we mean water that is not physically or chemically bound.

20 The formulation may be diluted by the addition of further amounts of water of up to an additional 20, 30, 40 or 50 wt% of water.

25 There is no direct correlation between the actual amount of water present in a composition and the amount of free water present. Free water does not include water which is not available such as water held within a gelled matrix or water of solvation of any components present in the composition.

30 In order to determine the amount of free water present in a composition, a standard loss-on-drying determination test may be carried out. A sample of the composition, usually about 10g, is weighed, and then

maintained at 60°C for 3 hours under a partial vacuum of 200 mbar (20 kPa). The sample is then re-weighed, and the weight lost determined.

5 The composition preferably comprises water softening actives that are soluble in polar solvents.

 Preferably the water-softening active is an acid. Preferably the acid is a carboxylic acid.

10

 Preferably, the water-softening active is a water-softening polymer. By the use of the phrase "a water-softening polymer" we mean polycarboxylic acid polymers, preferably polyacrylic polymers, based on acrylic acid
15 combined with or without other moieties. These include acrylic acid combined with; maleic acid (such as Sokalan CP5 and CP7 supplied by BASF or Acusol 479N supplied by Rohm & Haas); methacrylic acid (such as Colloid 226/35 supplied by Rhone-Poulenc); phosphonate (such as Casi 773
20 supplied by Buckman Laboratories); maleic acid and vinyl acetate (such as polymers supplied by Huls); acrylamide; sulfophenol methallyl ether (such as Aquatreat AR 540 supplied by Alco); 2-acrylamido-2-methylpropane sulfonic acid (such as Acumer 3100 supplied by Rohm & Haas or such
25 as K-775 supplied by Goodrich); 2-acrylamido-2-methylpropane sulfonic acid and sodium styrene sulfonate (such as K-798 supplied by Goodrich); methyl methacrylate; sodium methallyl sulfonate and sulfophenol methallyl ether (such as Alcoperse 240 supplied by Alco);
30 polymaleates (such as Belclene 200 supplied by FMC); polymethacrylates (such as Tamol 850 from Rohm & Haas); polyaspartates or ethylenediamine disuccinate and organo polyphosphonic acids and their salts such as the sodium

salts of aminotri(methylenephosphonic acid) and ethane 1-hydroxy-1,1-diphosphonic acid.

Preferably the polymer is a homopolymer of acrylic acid, blended with or without a polymaleic acid polymer or a polyacrylic/polymaleic acid copolymer. Preferably the polymer is a homopolymer of acrylic acid (such as those sold by Rohm & Haas under the Acusol trademark, such as Acusol WE).

Preferably, the water-softening polymer is partly neutralised. The term "partly neutralised" excludes neutralisation of more than 90% of the free acid (ideally carboxy) groups.

In a feature of the invention the water-softening polymer is partly neutralised with an organic base, preferably a C₁₋₁₆ alkanolamine (preferably a trialkanolamine). A preferred alkanol is ethanol.

Preferably the average MW (Mw) of the water-softening polymer should be greater than 1,000, ideally greater than 2,000, based upon the free acid.

Additional water-softening agents may be added to the composition. Preferably the additional water softening agent is a water-soluble water softening agent, which is organic monomeric polycarboxylic acids and their salts (such as citrates, gluconates, oxydisuccinates, glycerol mono- di- and trisuccinates, carboxymethyloxysuccinates, carboxymethyloxymalonates, dipicolinates and hydroxyethyliminodiacetates); sequestering agents (such as phosphonates and iminodisuccinates); radical scavengers (such as BHT); phosphonates (such as diethylenetriaminepenta (methylene

phosphonic acid) and its corresponding pentasodium salt, (available under the trade names Dequest 2060 and Dequest 2066 Monsanto Chemical Co.), DTPMP and DTPMA).

5 Preferably the composition of the invention comprises at least two water-softening actives, ideally at least one water-softening polymer and at least one monomeric polycarboxylic acid, preferably citric acid or a salt thereof.

10 Inorganic water-soluble water softening agents that may be present include alkali metal (generally sodium) carbonate.

15 The presence of surfactant and/or a source of active oxygen is not excluded from this invention. This invention may find use in the preparation of viscose detergent liquid compositions which contain a water-softening active and low amounts of water. Preferably the
20 composition contains less than 5% wt, ideally less than 1%wt, of a surfactant.

 The composition of the present invention may contain surfactants such as anionic, nonionic, amphoteric,
25 cationic or zwitterionic surfactants, or a mixture thereof.

 The composition, either encapsulated in a water-soluble polymer or not, can be used in fabric
30 washing(washing machines or handwashing) jointly with a detergent composition. Other applications, in machine dishwashing as anti limescale product or as anti limescale product in general for hard surfaces are also possible.

Suitable organic solvents include C3-C12 alkyl glycol, C3-C12 alkylglycol ethers and C1-C4 alcohols, such as methanol, ethanol and isopropanol. The solvent is typically present in an amount from about 0.5% to about 4.0%, preferably from about 0.75% to about 2.5%, and most preferably from about 1.0% to about 2.0% by weight of the composition. EGBE is available from Union Carbide under the trade name Butyl Cellosolve.

The organic solvent may be any organic solvent, although it is desirable that it is miscible with water. Examples of organic solvents are glycols, glycerine or an alcohol. Preferred organic solvents are C₁₋₄ alcohols such as ethanol or propanol, and C₂₋₄ glycols such as monoethylene glycol and monopropylene glycol.

The pH, as defined in the present context, is measured as 5% wt solutions in deionised water at 20°C. For optimum stability of these compositions, the pH, measured in the above-mentioned conditions, must be in the range of less than 7, from 3 to 7; ideally from 4.5 to 6.5, especially 5.0 to 5.7. The pH of these compositions can be regulated by the addition of a Bronsted acid or base.

The composition of the present invention contains less than 3 wt% water. Desirably the composition contains less than 2 wt% water, even more desirably less than 1 wt% water. Most preferably, the composition is substantially anhydrous. It will be appreciated that higher water content could be included when it is chemically or physically bound.

The present composition is especially suitable for use in a water-soluble container where the container is simply added to a large quantity of water and dissolves, releasing its contents. The favourable dissolution and dispersion properties of the composition of the present invention are particularly useful in this context.

Thus the present invention also provides a water-soluble container containing a composition as defined above.

A further feature of the invention is a method of softening water during a fabric washing process the method comprising adding a composition or container as defined herein to the fabric wash liquor.

The water-soluble container may comprise a thermoformed or injection moulded water-soluble polymer. It may also simply comprise a water-soluble film. Such containers are described, for example, in EP-A-524,721, GB-A-2,244,258, WO 92/17,381 and WO 00/55,068.

In all cases, the polymer is formed into a container or receptacle such as a pouch which can receive the composition, which is filled with the composition and then sealed, for example by heat sealing along the top of the container in vertical form-fill-processes or by laying a further sheet of water-soluble polymer or moulded polymer on top of the container and sealing it to the body of the container, for example by heat sealing.

Desirably the water-soluble polymer is a poly(vinyl alcohol) (PVOH). The PVOH may be partially or fully alcoholised or hydrolysed. For example, it may be from 40 to 100% preferably 70 to 92%, more preferably about

88%, alcoholised or hydrolysed, polyvinyl acetate. When the polymer is in film form, the film may be cast, blown or extruded.

5 The water-soluble polymer is generally cold water (20°C) soluble, but depending on its chemical nature, for example the degree of hydrolysis of the PVOH, may be insoluble in cold water at 20°C, and only become soluble in warm water or hot water having a temperature of, for
10 example, 30°C, 40C, 50°C or even 60°C. Because the composition contains less than 35 wt% water, the composition should not attack the PVOH container. However, it is preferable to add electrolyte into the
15 composition to increase the ionic strength of the composition and protect the PVOH container, such technique is taught in EP0519689. Suitable electrolytes are metal salts that freely dissociate upon dissolution, such as salts of alkali or alkaline earth metals.

20 The containers of the present invention find particular use where a unit-dosage form of the composition is required. The use of the container may place restrictions on its size. Thus, for example, a
25 suitable size for a container to be used in a laundry or dishwashing machine is a rounded cuboid container having a length of 1 to 5cm, especially 3.5 to 4.5cm, a width of 1.5 to 3.5cm, especially 2 to 3cm, and a height of 1 to 2cm, especially 1.25 to 1.75cm. The container may hold, for example, from 10 to 40g of the composition,
30 especially from 15, 20 or 30 to 40g of the composition for laundry use or from 15 to 20g of the composition for dishwashing use.

 Process for preparing suitable water-soluble
35 containers are described in WO0136290 and WO0216207.

The viscosity of the composition of the present invention, measured using a Brookfield viscometer, model DV-II+, with spindle S31 at 12 RPM and at 20°C, is
5 desirably 500 to 1,000,000 cps, more especially 1500 to 500,000 cps, especially 10,000 to 40,000 cps.

The present invention is now further described in the following Examples, in which all of the parts are
10 parts by weight.

[illegible]

CLAIMS

1. A liquid water-softening composition comprising:
 - a) at least one water-softening active; and
 - b) an organic solvent;said composition containing less than 35 wt% water.
2. A composition according to claim 1 wherein the at least one water-softening active is an acid.
3. A composition according to claim 1 or 2 wherein the at least one water-softening active is a carboxylic acid.
4. A composition according to claim 2 or 3 wherein the acid is partly neutralised.
5. A composition according to any one of claims 1 to 4 wherein at least one water-softening active is a water-softening polymer.
6. A composition according to claim 5 wherein the water-softening polymer is a polycarboxylic acid polymer
7. A composition according to claim 6 wherein the polycarboxylic acid polymer is a polyacrylic polymer.
8. A composition according to any one of the preceding claims wherein the acid water-softening active is partly neutralised by an organic base.
9. A composition according to claim 8 wherein the acid water-softening active that is neutralised is citric

acid.

10. A composition according to claim 8 or 9 wherein the organic base is an alkanolamine.

11. A composition according to claim 10 in which the alkanolamine is monoethanolamine, diethanolamine or triethanolamine.

12. A composition according to any one of the preceding claims wherein the organic solvent is a glycol, glycolether glycerine, or an alcohol or a mixture thereof.

13. A composition according to claim 12 wherein the organic solvent is glycerine, monopropylene glycol or ethanol.

14. A composition according to any one of the preceding claims which contains less than 15 wt% of free water.

15. A composition according to any one of the preceding claims which comprises from 10 to 20 wt% of organic solvent.

16. A composition according to any one of the preceding claims which has a pH when measured as a 5%wt solution in deionised water at 20°C of less than 7, ideally 5.0 to 5.7.

17. A composition according to any one of the preceding claims which contains a monomeric polycarboxylic acid.

18. A composition according to claim 17 wherein the monomeric polycarboxylic acid is citric acid.
- 5 19. A water-soluble container containing a composition as defined in any one of the preceding claims.
20. A container according to claim 19 which comprises a thermoformed or injection moulded water-soluble polymer.
- 10 21. A container according to claim 19 or 20 wherein the water-soluble polymer is a poly (vinyl alcohol).

ABSTRACT

WATER-SOFTENING PRODUCT

5
A liquid water-softening composition comprising:
a) at least one water-softening active; and
10 b) an organic solvent;
said composition containing less than 35 wt% water.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.